


RIDEMAX FL 693 M



TIRE SIZE	710/50 R 30.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	173 D

DIMENSIONES US STANDARD

CÓDIGO USA	94037049	RC (IN)	178.5
SW (IN)	28.6	RIM REC	AG 24.00
OD (IN)	58.5	RIM ALT	AG 20.00
SLR (IN)	26.6	ECE	E4-106R-001498

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	4890	5560	6750	7800	8990	10180	10980	12170	13230
40	5300	6020	7310	8450	9740	11030	11890	13180	14330
30	6430	7290	8850	10240	11790	13360	14400	15960	17340
25	7220	8190	9940	11510	13260	15010	16180	17930	19490
15	8390	9510	11550	13360	15400	17440	18790	20830	22640
5	9550	10840	13160	15220	17550	19860	21420	23730	25790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.