


# FL 639

<b>TIRE SIZE</b>	<b>600/50 R 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPREADER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	168 B ; 156 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1172	<b>ECE</b>	E11-106R-006478
<b>SLR (MM)</b>	521	<b>SRI</b>	550
<b>RC (MM)</b>	3592		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
<b>50 FR</b>	2180	2490	2800	3125	3450	3725	4000	4310	4625	4885	5150	5375	5600
<b>50 DW</b>	1550	1775	2000	2215	2430	2615	2800	3025	3250	3450	3650	3825	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.