

## AGRIMAX RT 657

|                  |                                          |
|------------------|------------------------------------------|
| <b>TIRE SIZE</b> | <b>320/65 R 18</b>                       |
| <b>UM</b>        | US STANDARD                              |
| <b>MACHINERY</b> | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| <b>VERSION</b>   | STANDARD                                 |
| <b>TL/TT</b>     | TL                                       |
| <b>LI/SS</b>     | 109 A8/B                                 |



### DIMENSIONS US STANDARD

|                 |          |                                      |                |
|-----------------|----------|--------------------------------------|----------------|
| <b>USA CODE</b> | 94027606 | <b>RIM REC</b>                       | W 10           |
| <b>SW (IN)</b>  | 12.6     | <b>RIM ALT</b>                       | W 9 ; W 11     |
| <b>OD (IN)</b>  | 34.4     | <b>ECE</b>                           | E4-106R-000636 |
| <b>SLR (IN)</b> | 15.4     | <b>TRA CODE</b>                      | R1W            |
| <b>RC (IN)</b>  | 101.9    | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 40.95          |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 1320 | 1530 | 1730 | 1920 | 2090 | 2270 |
| <b>25</b>   | 1320 | 1530 | 1730 | 1920 | 2090 | 2270 |
| <b>20</b>   | 1420 | 1640 | 1850 | 2050 | 2250 | 2440 |
| <b>5 LT</b> | 1770 | 2050 | 2330 | 2570 | 2810 | 3050 |
| <b>5 HT</b> | 1420 | 1640 | 1850 | 2050 | 2250 | 2440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.