

# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>620/75 R 26 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HARVESTER / COTTON PICKER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	166 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	625	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1590	<b>ECE</b>	E4-106R-001419
<b>SLR (MM)</b>	730	<b>SRI</b>	750
<b>RC (MM)</b>	4851		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	2440	2810	3445	3765	4135	4505	4880	5300
40	2440	2810	3445	3765	4135	4505	4880	5300
30	2615	3010	3690	4030	4430	4825	5225	5675
15 CYC	4025	4635	5685	6210	6825	7435	8050	8745
10 CYC	4390	5060	6205	6775	7445	8110	8780	9540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.