


MULTIMAX MP 522

| | |
|---------------------|--|
| TIRE SIZE | 380/75 R 20 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | KOMPAKTLADER / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 148 A8/B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA-CODE | 94045877 | RC (IN) | 128.0 |
| SW (IN) | 15.1 | RIM REC | W 12 |
| OD (IN) | 42.3 | RIM ALT | W 11; 11; 12 |
| SLR (IN) | 19.0 | ECE | E11-106R-002963 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 35 | 41 | 46 | 52 | 55 | 58 | 61 | 64 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 3310 | 3900 | 4500 | 5080 | 5680 | 6310 | 6620 | 6940 | - | - |
| 25 | 3310 | 3900 | 4500 | 5080 | 5680 | 6310 | 6620 | 6940 | - | - |
| 20 | 3550 | 4190 | 4840 | 5490 | 6130 | 6780 | 7100 | 7430 | - | - |
| 15 | 3680 | 4350 | 5030 | 5700 | 6370 | 7040 | 7390 | 7720 | - | - |
| 5 CYC. | 4080 | 4980 | 5890 | 6790 | 7690 | 8600 | 9060 | 9510 | 9960 | 10430 |
| STATIC | 6260 | 7650 | 9040 | 10430 | 11820 | 13210 | 13900 | 14590 | 15290 | 15980 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.