

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>420/70 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	133 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	418	<b>RIM REC</b>	W 13
<b>OD (MM)</b>	1349	<b>RIM ALT</b>	W 12; W 14 L
<b>SLR (MM)</b>	604	<b>ECE</b>	E11-106R-005520
<b>RC (MM)</b>	4020	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1135	1320	1505	1690	1875	2060
50	1195	1390	1585	1780	1975	2165
40	1245	1450	1650	1855	2060	2260
30	1305	1520	1735	1945	2160	2370
10 LT	1525	1770	2020	2270	2520	2765
10 HT	1305	1520	1735	1945	2160	2370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.