


# AGRIMAX FORTIS

<b>TIRE SIZE</b>	<b>600/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 D ; 161 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94032952	<b>RC (IN)</b>	189.4
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	63.1	<b>RIM ALT</b>	DW 18 L ; W 18 L
<b>SLR (IN)</b>	28.5	<b>ECE</b>	E4-106R-001400

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	4500	5250	5910	6560	7220	7780	8620	9370
30	4730	5520	6210	6900	7580	8180	9060	9840
25	4890	5710	6430	7140	7860	8470	9380	10200
20	5180	6040	6800	7550	8310	8950	9920	10780
5 LT	6030	7030	7910	8800	9680	10430	11550	12550
5 HT	5180	6040	6800	7550	8310	8950	9920	10780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.