

AGRIMAX FORCE

TIRE SIZE	IF 380/80 R 38
UM	IS STANDARD
MACHINERY	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	149 D



DIMENSIONS IS STANDARD

SW (MM)	380	RIM REC	W 12
OD (MM)	1573	RIM ALT	W 11 ; W 13
SLR (MM)	725	ECE	E11-106R-005715
RC (MM)	4793	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1385	1595	1830	2070	2305	2540	2780	2955
FROM 65 TO 40	1525	1755	2015	2275	2535	2795	3055	3250
30	1585	1825	2095	2365	2635	2905	3175	3380
20	1645	1895	2175	2455	2735	3015	3295	3510
10	1935	2225	2555	2885	3215	3545	3875	4125
*UPTO 10 CYC WITH FRONT LOADER	2135	2455	2820	3185	3545	3910	4275	4550
10HT	1585	1825	2095	2365	2635	2905	3175	3380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.