

# TR 171

|                     |                  |
|---------------------|------------------|
| <b>TIRE SIZE</b>    | <b>14.9 - 24</b> |
| <b>UM</b>           | US STANDARD      |
| <b>CONSTRUCTION</b> | ⊠ BIAS           |
| <b>MACHINERY</b>    | TRAKTOR          |
| <b>VERSION</b>      | STANDARD         |
| <b>TIRE TYPE</b>    | TT               |
| <b>LI/SS</b>        | 119 A8           |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94025626 | <b>RC (IN)</b> | 149.3           |
| <b>SW (IN)</b>  | 15.4     | <b>RIM REC</b> | W 13            |
| <b>OD (IN)</b>  | 49.8     | <b>RIM ALT</b> | W 11; W 12      |
| <b>SLR (IN)</b> | 22.6     | <b>ECE</b>     | E11-106R-003377 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>20</b> |
| 25               | 3000      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.