


AGRIMAX PROHARVEST

TYRE SIZE	VF 620/70 R 26
UM	US STANDARD
CONSTRUCTION	 RADIAL
VERSION	STEEL BELTED
TYRE TYPE	TL
LI/SS	173 D



DIMENSIONS US STANDARD

USA CODE	94516605	RC (IN)	180.7
SW (IN)	24.4	RIM REC	DW 21 B
OD (IN)	60.2	RIM ALT	DW 20 B; DW 23 B
SLR (IN)	26.4	ECE	E11-106R-0011721

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41
45	5610	6530	7440	8360	9260	10170	11220	11870	13040
FROM 40 TO 25	6160	7160	8170	9170	10170	11180	12320	13040	14330
20	6290	7310	8330	9360	10380	11410	12580	13300	14620
12	6420	7450	8500	9550	10580	11630	12820	13570	14900
5	6780	7880	8990	10100	11200	12300	13560	14350	15760
*UPTO 20 CYC	7000	8130	9280	10420	11550	12700	14000	14810	16270
*UPTO 10 CYC	8360	9710	11080	12430	13800	15160	16710	17680	19420
*UPTO 5 CYC	9160	10650	12140	13620	15120	16610	18310	19380	21280
10HT	6290	7310	8330	9360	10380	11410	12580	13300	14620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.