


# AGRIMAXFACTOR

<b>TYRE SIZE</b>	<b>600/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	152 D ; 155 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94070152	<b>RC (IN)</b>	187.6
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	63.1	<b>RIM ALT</b>	DW 18 L ; W 18 L
<b>SLR (IN)</b>	28.4	<b>ECE</b>	E11-106R-007524

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
40	4310	5020	5720	6430	7130	7830
30	4530	5270	6010	6750	7480	8220
25	4710	5470	6240	7010	7780	8540
20	4960	5760	6580	7390	8200	9010
5 LT	5780	6720	7660	8610	9560	10490
5 HT	4960	5760	6580	7390	8200	9010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.