


FORESTMAX

TYRE SIZE	540/540 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STEEL BELTED
TYRE TYPE	TL
LI/SS	149 A8 ; 146 B



DIMENSIONS IS STANDARD

SW (MM)	550	RIM REC	W 18 L
OD (MM)	1413	ECE	E11-106R-008830
SLR (MM)	649	SRI	675
RC (MM)	4247		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4
50	2040	2280	2340	2580	2790	2880	3000
40	2210	2470	2535	2795	3020	3120	3250
30	2370	2645	2715	2995	3235	3345	3480
25	2455	2745	2815	3105	3355	3470	3610
20	2720	3040	3120	3440	3720	3840	4000
15	2965	3310	3395	3745	4050	4185	4355
10	3315	3705	3800	4190	4530	4680	4875
10 FORESTRY SERVICE	-	-	-	-	-	-	4000
0 FORESTRY SERVICE	-	-	-	-	-	-	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.