


# AW 711

<b>TIRE SIZE</b>	<b>305/70 R 16.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENT MACHINERY / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STUBBLE RESISTANT
<b>TL/TT</b>	TL
<b>LI/SS</b>	148 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94053506	<b>RC (IN)</b>	100.5
<b>SW (IN)</b>	12.8	<b>RIM REC</b>	9.75
<b>OD (IN)</b>	33.5	<b>ECE</b>	E11-106R-002995
<b>SLR (IN)</b>	14.6		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73
30	2080	2710	3340	3820	4450	5070	5420	5970	6540	6940
25	2080	2710	3340	3820	4450	5070	5420	5970	6540	6940
20	2340	3040	3740	4290	4980	5690	6070	6700	7320	7780
15	2480	3230	3970	4550	5290	6040	6450	7110	7770	8270
10	2630	3420	4210	4820	5610	6390	6830	7530	8230	8750
5	2920	3790	4670	5360	6230	7100	7580	8370	9150	9720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.