

MULTIMAX MP 522

440/80 R 24**UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** KÜÇÜK YÜKLEYİCİ / TELESKOPIK
YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ /
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

161 A8/B

**UNDEFINED IS STANDARD**

SW (MM)	441	RIM REC	DW 14 L
OD (MM)	1314	RIM ALT	DW 13; DW 13 L; DW 15 L
SLR (MM)	586	ECE	E11-106R-002966
RC (MM)	3958	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2220	2640	3010	3425	3840	4120	4625	-	-
40	2220	2640	3010	3425	3840	4120	4625	-	-
30	2380	2825	3220	3665	4110	4410	4950	-	-
25	2465	2930	3340	3800	4265	4575	5135	-	-
10 CYC.	2710	3335	3925	4515	5140	5590	6320	6665	6940
STATIC	4150	5110	6015	6920	7875	8570	9685	10215	10640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.