


EARTHMAX SR 30

| | |
|--------------|--|
| TIRE SIZE | 20.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | DÚMPER RIGIDO / BULDÓCER |
| VERSIÓN | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 177 B ; 186 A2 |



DIMENSIONES IS STANDARD

| | | | |
|----------|-----------|-------------|-----------|
| OD (MM) | 1487 | RIM ALT | 17.00/1.7 |
| SLR (MM) | 663 | TRA CODE | E3/L3 |
| RC (MM) | 4439 | STAR RATING | ★★★ |
| RIM REC | 17.00/2.0 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|------|------|------|------|------|------|
| 50 | 5800 | 6150 | 6500 | 6700 | 6900 | 7300 |
| 10 | 8000 | 8250 | 8750 | 9000 | 9500 | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.