

AGRIMAX RT 855

TIRE SIZE	280/85 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	115 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94044658	RC (IN)	126.9
SW (IN)	11.5	RIM REC	W 10
OD (IN)	42.8	RIM ALT	W 9
SLR (IN)	19.4	ECE	E4-106R-000611

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1480	1720	1960	2200	2450	2680
25	1480	1720	1960	2200	2450	2680
20	1590	1850	2110	2370	2620	2880
5 LT	1980	2300	2620	2950	3270	3590
5 HT	1590	1850	2110	2370	2620	2880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.