

# MULTIMAX MP 513

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 425/75 R 20 MPT  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | UNIVERSAL VEHICLE / FERTILIZER TRUCK / UNIVERSAL VEHICLE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 148 G  |



## DIMENSIONS IS STANDARD

|                 |       |                |                                |
|-----------------|-------|----------------|--------------------------------|
| <b>SW (MM)</b>  | 421   | <b>RIM REC</b> | 13                             |
| <b>OD (MM)</b>  | 1146  | <b>RIM ALT</b> | 13 SDC; 11 SDC; 12 SDC; 11; 12 |
| <b>SLR (MM)</b> | 518.5 | <b>ECE</b>     | E11-54R-0016141                |
| <b>RC (MM)</b>  | 3465  |                |                                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6  | 2.0  | 2.5  | 3.0  | 3.5  | 4.0  |
|------------|------|------|------|------|------|------|
| 90         | 1540 | 1810 | 2150 | 2490 | 2820 | 3150 |
| 65         | 1675 | 1965 | 2335 | 2705 | 3060 | 3420 |
| 40         | 1775 | 2085 | 2475 | 2865 | 3245 | 3625 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.