

# AW 708

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	149 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94010356	<b>RC (IN)</b>	100.9
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	AG 13.00
<b>OD (IN)</b>	34.4	<b>ECE</b>	E4-106R-001543
<b>SLR (IN)</b>	15.0	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>65</b>
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.