


RIDEMAX FL 693 M

VF 400/45 R 17.5

| | |
|--------------|--|
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TANKER / RÖMÖRK / UYGULAMALI MAKINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 142 D |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 400 | RIM REC | 14.00 |
| OD (MM) | 800 | ECE | E11-106R-007199 |
| SLR (MM) | 357 | SRI | 390 |
| RC (MM) | 2448 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|
| 70 | 1040 | 1260 | 1405 | 1620 | 1840 | 2005 | 2200 | 2415 |
| 65 | 1140 | 1380 | 1540 | 1780 | 2015 | 2200 | 2415 | 2650 |
| 50 | 1385 | 1670 | 1865 | 2155 | 2440 | 2665 | 2925 | 3210 |
| 40 | 1555 | 1875 | 2095 | 2420 | 2740 | 2995 | 3285 | 3605 |
| 30 | 1725 | 2085 | 2325 | 2685 | 3045 | 3325 | 3645 | 4005 |
| 25 | 1805 | 2180 | 2435 | 2810 | 3185 | 3480 | 3815 | 4190 |
| 10 | 2055 | 2485 | 2770 | 3200 | 3630 | 3960 | 4345 | 4770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.