


# MULTIMAX MP 525

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>405/70 R 20</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL       |
| <b>MACHINERY</b>    | UNIVERSALFORDON /<br>TELESKOPLASTARE /<br>KOMPAKTHJULLASTARE /<br>TELESKOPLASTARE / VÄGHYVLARE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 J ; 168 A2   |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94072873 | <b>RIM REC</b> | 13              |
| <b>OD (IN)</b>  | 42.4     | <b>RIM ALT</b> | 12; 13 SDC      |
| <b>SLR (IN)</b> | 19.0     | <b>ECE</b>     | E11-54R-0020576 |
| <b>RC (IN)</b>  | 128.3    |                |                 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>87</b> |
| 62               | 7830      |
| 5                | 12350     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.