


# RIDEMAX FL 690

**30.5L R 32**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKER / RÖMORK / UYGULAMALI MAKINE / RÖMORK
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	184 A8 ; 181 B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	790	<b>RIM REC</b>	DH 27 B
<b>OD (MM)</b>	1800	<b>RIM ALT</b>	DW 27 B
<b>SLR (MM)</b>	806	<b>ECE</b>	E11-106R-002986
<b>RC (MM)</b>	5430	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.0
50	3795	4375	5280	5695	6520	7260	7920	8250
40	4370	5030	6075	6550	7500	8355	9115	9490
30	4935	5685	6865	7405	8475	9440	10300	10725
25	5205	5995	7240	7805	8935	9950	10855	11305
10	6040	6955	8400	9055	10365	11550	12600	13120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.