


# EARTHMAX SR 45 PLUS

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>33.00 R 51</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | САМОСВАЛ С ЖЕСТКОЙ РАМОЙ   |
| <b>VERSION</b>      | HEAT RESISTANT COMPOUND  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 235 B  |



## РАЗМЕРЫ US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94073320 | <b>RIM REC</b>     | 24.00/5.0 |
| <b>OD (IN)</b>  | 120.7    | <b>TRA CODE</b>    | E4        |
| <b>SLR (IN)</b> | 53.9     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>  | 366.7    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 66000 | 68000 | 71500 | 74000 | 76000 | 78500 | 80500 | 82500 | 85500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.