


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 650/85 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	182 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94513543	<b>RC (IN)</b>	240.9
<b>SW (IN)</b>	26.4	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	81.5	<b>RIM ALT</b>	DW 20 B; DW 21 B
<b>SLR (IN)</b>	34.9	<b>ECE</b>	E11-106R-0010579

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	8520	9890	11250	12790	14150	15510	17050
FROM 40 TO 25	9370	10870	12370	14050	15550	17050	18740
20	9560	11080	12610	14330	15860	17380	19110
12	9740	11300	12850	14620	16170	17720	19490
5	10310	11950	13600	15450	17110	18750	20610
UPTO 20 CYC	10630	12320	14030	15940	17650	19340	21260
UPTO 10 CYC	12690	14720	16740	19040	21060	23090	25380
UPTO 5CYC	13910	16130	18350	20870	23080	25310	27820
5 HT	9560	11080	12610	14330	15860	17380	19110

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.