

# FLOTATION 648

**800/45 - 26.5**

<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALYA MAKINESİ / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKİNE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	164 A8/160 B
	177 A8/173 B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	800	<b>RIM REC</b>	AG 28.00
<b>OD (MM)</b>	1393	<b>ECE</b>	E4-106R-002280
<b>SLR (MM)</b>	631	<b>PR</b>	16
<b>RC (MM)</b>	4185		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.80	2.00	2.20
10 FR	9085	9665	10220
20 FR	8175	8700	9200
30 FR	7270	7735	8175
40 FR	6490	6905	7300
50 FR	5840	6215	6500
10 DW	6225	6620	7000
20 DW	5600	5960	6300
30 DW	4980	5300	5600
40 DW	4445	4730	5000
50 DW	4000	4225	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.