

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 520/70 R 34 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 148 D |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94063192 | RC (IN) | 194.0 |
| SW (IN) | 20.3 | RIM REC | W 16 L |
| OD (IN) | 64.6 | RIM ALT | W 15 L; W 18 L |
| SLR (IN) | 29.1 | ECE | E11-106R-005831 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 90 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 3820 | 4450 | 5070 | 5700 | 6330 | 6940 |
| 30 | 4020 | 4670 | 5330 | 5990 | 6920 | 7300 |
| 25 | 4190 | 4870 | 5560 | 6240 | 6920 | 7610 |
| 20 | 4400 | 5110 | 5840 | 6560 | 7270 | 7990 |
| 5 LT | 5130 | 5960 | 6800 | 7640 | 8480 | 9310 |
| 5 HT | 4400 | 5110 | 5840 | 6560 | 7270 | 7990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.