

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>380/70 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	127 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94063178	<b>RC (IN)</b>	152.9
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	50.9	<b>RIM ALT</b>	W 11; W 13
<b>SLR (IN)</b>	23.1	<b>ECE</b>	E11-106R-005829

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>40</b>	2130	2470	2820	3160	3520	3860
<b>30</b>	2240	2600	2970	3330	3690	4060
<b>25</b>	2340	2710	3100	3470	3860	4230
<b>20</b>	2450	2840	3250	3650	4050	4440
<b>5 LT</b>	2840	3320	3780	4240	4710	5170
<b>5 HT</b>	2450	2840	3250	3650	4050	4440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.