


MULTIMAX MP 527

| | |
|---------------------|--|
| TIRE SIZE | 460/70 R 24 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 159 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-------------------|
| SW (MM) | 465 | RIM REC | DW 15 L |
| OD (MM) | 1254 | RIM ALT | DW 14 L ; DW 16 L |
| SLR (MM) | 574 | ECE | E11-106R-002983 |
| RC (MM) | 3801 | SRI | 600 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.5 | 4.0 | 4.2 | 4.4 |
|------------|------|------|------|------|------|------|------|------|-------|
| 50 | 2100 | 2495 | 2845 | 3240 | 3635 | 3895 | 4375 | - | - |
| 40 | 2100 | 2495 | 2845 | 3240 | 3635 | 3895 | 4375 | - | - |
| 30 | 2250 | 2675 | 3050 | 3470 | 3890 | 4170 | 4685 | - | - |
| 25 | 2335 | 2775 | 3160 | 3600 | 4035 | 4330 | 4860 | - | - |
| 10 CYC. | 2565 | 3155 | 3710 | 4270 | 4860 | 5285 | 5975 | 6305 | 6565 |
| STATIC | 3930 | 4835 | 5690 | 6545 | 7450 | 8105 | 9160 | 9665 | 10065 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.