


AGRIMAX RT 600

TIRE SIZE	620/75 R 26
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / TRACTOR / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	167 A8/B



DIMENSIUNI US STANDARD

USA CODE	94050444	RC (IN)	191.0
SW (IN)	24.6	RIM REC	DW 20 B
OD (IN)	62.6	ECE	E11-106R-002993
SLR (IN)	28.7		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	49	55
30	5530	6370	7810	8530	9380	10220	11060	12010	-	-
25	5530	6370	7810	8530	9380	10220	11060	12010	-	-
20	5920	6820	8370	9140	10040	10930	11840	12860	-	-
5 LT	7420	8540	10470	11440	12570	13690	14830	16100	-	-
5 HT	5920	6820	8370	9140	10040	10930	11840	12860	-	-
5 CYC.	-	9090	11650	12780	14810	16250	17780	19310	19610	20420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.