


# AGRIMAX FORTIS



<b>TYRE SIZE</b>	<b>800/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	178 D ; 181 A8

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	798	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	2085	<b>RIM ALT</b>	DW 27 B
<b>SLR (MM)</b>	912	<b>ECE</b>	E4-106R-001424
<b>RC (MM)</b>	6202	<b>SRI</b>	975

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3600	4200	4725	5250	5775	6225	6900	7500
50	3780	4410	4965	5515	6065	6540	7245	7875
40	3960	4620	5200	5775	6355	6850	7590	8250
30	4140	4830	5435	6040	6645	7160	7935	8625
10 LT	4825	5630	6335	7035	7740	8345	9250	10050
10 HT	4140	4830	5435	6040	6645	7160	7935	8625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.