


# RM 500

<b>TIRE SIZE</b>	<b>500/80 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 A8 ; 164 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94063697	<b>RC (IN)</b>	171.5
<b>SW (IN)</b>	19.8	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	58.9	<b>RIM ALT</b>	W 15 L
<b>SLR (IN)</b>	25.0	<b>ECE</b>	E11-106R-005990

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46
<b>25 FREE ROLLING</b>	6110	7040	7830	9710	11120	12840	14560	15650
<b>25 DRIVE WHEEL</b>	4300	4960	5510	6830	7830	9040	10250	11020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.