

# AW 705

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>14.0/65 - 16</b>  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | EMPACADORA DE HENO /<br>MAQUINARIA AGRÍCOLA / REMOLQUE<br>/ COSECHADORA / MAQUINARIA<br>AGRÍCOLA |
| <b>VERSIÓN</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TT   |
| <b>LI/SS FREE ROLLING</b> | 134 A8   |



## DIMENSIONES IS STANDARD

|                 |      |                |      |
|-----------------|------|----------------|------|
| <b>SW (MM)</b>  | 353  | <b>RIM REC</b> | 11.0 |
| <b>OD (MM)</b>  | 870  | <b>PR</b>      | 10   |
| <b>SLR (MM)</b> | 388  |                |      |
| <b>RC (MM)</b>  | 2549 |                |      |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>2.80</b> |
|-------------------|-------------|
| 10 FR             | 2970        |
| 25 FR             | 2525        |
| 30 FR             | 2375        |
| 40 FR             | 2120        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.