

AW 702

| | |
|---------------------------|---|
| TIRE SIZE | 10.5/80 - 18 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 140 A8 |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 275 | RIM REC | W 9 |
| OD (MM) | 885 | RIM ALT | W 8; 9 |
| SLR (MM) | 395 | ECE | E11-106R-007039 |
| RC (MM) | 2593 | PR | 16 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.80 |
|-------------------|-------------|
| 10 FR | 3500 |
| 25 FR | 2975 |
| 30 FR | 2800 |
| 40 FR | 2500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.