


AGRIMAX V- FLECTO

TIRE SIZE	VF 600/65 R 34 NRO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	169 D



DIMENSIONES IS STANDARD

SW (MM)	597	RIM REC	DW 21 B
OD (MM)	1644	RIM ALT	DW 20 B
SLR (MM)	731	ECE	E11-106R-007603
RC (MM)	4952	SRI	775

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.8	2.0	2.4
70	2430	2800	3220	3590	4010	4380	4910	5275
FROM 65 TO 40	2670	3075	3540	3945	4410	4815	5395	5800
30	2725	3135	3610	4025	4500	4910	5505	5915
20	2775	3200	3680	4105	4585	5005	5610	6030
10	2935	3385	3895	4340	4850	5300	5935	6380
*UPTO 10 CYC WITH FRONT LOADER	3740	4305	4955	5525	6175	6740	7555	8120
10 HT	2725	3135	3610	4025	4500	4910	5505	5915

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.