


# MULTIMAX MP 527

**360/70 R 18 IND**

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	KÜÇÜK YÜKLEYİCİ / TELESKOPIK YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ / TELESKOPIK YÜKLEYİCİ
VERSION	STANDARD
TIRE TYPE	TL
	142 A8/B



## UNDEFINED IS STANDARD

SW (MM)	360	RIM REC	11
OD (MM)	969	RIM ALT	W10; 11 SDC; W11; 12; 12 SDC
SLR (MM)	439	ECE	E11-106R-002996
RC (MM)	2887	SRI	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1275	1515	1725	1965	2200	2360	2650	-	-
40	1275	1515	1725	1965	2200	2360	2650	-	-
30	1365	1620	1850	2105	2360	2530	2840	-	-
25	1415	1680	1915	2180	2445	2625	2945	-	-
10 CYC.	1555	1910	2250	2585	2945	3200	3620	3820	3975
STATIC	2380	2930	3445	3965	4515	4910	5550	5855	6095

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.