


# AS 504

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	126 A8
<b>LI/SS FREE ROLLING</b>	139 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94018758	<b>RC (IN)</b>	100.0
<b>SW (IN)</b>	11.4	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	34.1	<b>ECE</b>	E11-106R-003510
<b>SLR (IN)</b>	15.0	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	70
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360
5 DW	5250
15 DW	4460
20 DW	4200
25 DW	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.