


FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 650/65 - 30.5 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA |
| VERSIÓN | HD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 167 A8/163 B |
| LI/SS FREE ROLLING | 179 A8/175 B |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94030149 | RC (IN) | 194.3 |
| SW (IN) | 26.4 | RIM REC | AG 20.00 |
| OD (IN) | 65.4 | ECE | E11-106R-004562 |
| SLR (IN) | 28.0 | PR | 16 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 26 | 29 | 32 |
|--------------|-------|-------|-------|
| 5 FR | 21260 | 22620 | 23920 |
| 10 FR | 19140 | 20360 | 21530 |
| 20 FR | 17010 | 18100 | 19140 |
| 25 FR | 15190 | 16160 | 17080 |
| 30 FR | 13670 | 14540 | 15210 |
| 5 DW | 14960 | 15910 | 16820 |
| 10 DW | 13460 | 14320 | 15130 |
| 20 DW | 11960 | 12730 | 13460 |
| 25 DW | 10680 | 11360 | 12010 |
| 30 DW | 9610 | 10230 | 10750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.