

AGRIMAX FORCE

TIRE SIZE	IF 710/60 R 30 CFO
UM	IS STANDARD
MACHINERY	ERNTemaschine / HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D



ABMESSUNGEN IS STANDARD

SW (MM)	708	ECE	E4-106R-001407
OD (MM)	1614	SRI	775
SLR (MM)	714	TRA CODE	R1W
RC (MM)	4814	TREAD DEPTH (MM)	58,5
RIM REC	DW 25 B		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2340	2695	3105	3460	3870	4225	4735	5095
FROM 65 TO 40	2575	2965	3415	3805	4255	4645	5205	5600
30	2675	3080	3550	3955	4425	4830	5410	5820
20	2780	3200	3685	4105	4595	5015	5620	6045
10	3270	3765	4335	4830	5400	5895	6610	7110
UPTO 30 CYC	3345	3850	4435	4945	5530	6035	6765	7280
UPTO 15 CYC	3990	4595	5290	5895	6595	7195	8065	8680
UPTO 10 CYC	4375	5040	5805	6465	7230	7895	8845	9520
10 HT	2675	3080	3550	3955	4425	4830	5410	5820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.