


# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>425/55 R 17 MPT</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VEHÍCULO UNIVERSAL / CAMIÓN DE FERTILIZANTES / VEHÍCULO UNIVERSAL
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 A8/B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	421	<b>RIM REC</b>	13
<b>OD (MM)</b>	900	<b>RIM ALT</b>	13.00
<b>SLR (MM)</b>	399	<b>ECE</b>	E11-106R-006433
<b>RC (MM)</b>	2705		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.5	4.0
50	1035	1275	1515	1725	1965	2200	2440	2650
40	1035	1275	1515	1725	1965	2200	2440	2650
30	1110	1365	1620	1850	2105	2360	2530	2840
25	1150	1415	1680	1915	2180	2445	2625	2945

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.