


AGRIMAX RT 765

TIRE SIZE	710/70 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	173 D ; 176 A8



DIMENSIONS US STANDARD

USA CODE	94033157	RC (IN)	243.1
SW (IN)	28.2	RIM REC	DW 23 B
OD (IN)	81.1	RIM ALT	DW 25 B
SLR (IN)	36.3	ECE	E4-106R-000807

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	6880	8020	9030	10030	11030	11890	13180	14300
30	7230	8430	9480	10540	11600	12490	13840	15050
25	7520	8770	9870	10960	12060	13000	14410	15650
20	7910	9240	10380	11540	12700	13680	15170	16480
5 LT	9230	10760	12100	13450	14790	15940	17670	19200
5 HT	7910	9240	10380	11540	12700	13680	15170	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.