


AGRIMAX TURF RT 333

	280/70 R 16
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ÜZÜM HASAT MAKINESİ / MEYVE HASADI MAKINESİ / KÜÇÜK TRAKTÖR / TRAKTÖR / BIÇERDÖVER
VERSION	STANDARD
TIRE TYPE	TL
	112 A8 ; 112 B



UNDEFINED US STANDARD

USA CODE	94065714	RC (IN)	93.3
SW (IN)	11.4	RIM REC	W9
OD (IN)	31.5	RIM ALT	W 8 ; W 10
SLR (IN)	14.1	ECE	E11-106R-006472

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1170	1330	1530	1730	1930	2130	2330	2470
25	1170	1330	1530	1730	1930	2130	2330	2470
20	1250	1430	1640	1850	2070	2280	2490	2650
5 LT	1570	1800	2060	2330	2590	2850	3120	3320
5 HT	1250	1430	1640	1850	2070	2280	2490	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.