

# FLOTATION 647

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | 520/50 - 17                             |
| <b>UM</b>                 | US STANDARD                             |
| <b>CONSTRUCTION</b>       | ⊠ BIAS                                  |
| <b>MACHINERY</b>          | OUTILLAGE AGRICOLE / OUTILLAGE AGRICOLE |
| <b>VERSION</b>            | STANDARD                                |
| <b>TIRE TYPE</b>          | TL                                      |
| <b>LI/SS DRIVE WHEEL</b>  | 147 B                                   |
| <b>LI/SS FREE ROLLING</b> | 159 B                                   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94063314 | <b>RC (IN)</b> | 114.4           |
| <b>SW (IN)</b>  | 20.3     | <b>RIM REC</b> | AG 16.00        |
| <b>OD (IN)</b>  | 38.0     | <b>ECE</b>     | E11-106R-005770 |
| <b>SLR (IN)</b> | 16.8     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58   |
|-----------|------|
| 30 FR     | 9650 |
| 30 DW     | 6800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.