


# AS 504

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>6.5/80 - 12</b>   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | TELESKOPLASTARE / ÅKERSLÄP /<br>ARBETSFORDON / TELESKOPLASTARE                         |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TT   |
| <b>LI/SS DRIVE WHEEL</b>  | 80 A8  |
| <b>LI/SS FREE ROLLING</b> | 93 A8  |



## DIMENSIONER IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 169  | <b>RIM REC</b> | 5 J            |
| <b>OD (MM)</b>  | 608  | <b>RIM ALT</b> | 5 JA           |
| <b>SLR (MM)</b> | 283  | <b>ECE</b>     | E4-106R-002180 |
| <b>RC (MM)</b>  | 1836 | <b>PR</b>      | 6              |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.60</b> |
|-------------------|-------------|
| 10 FR             | 910         |
| 25 FR             | 775         |
| 30 FR             | 730         |
| 40 FR             | 650         |
| 10 DW             | 630         |
| 25 DW             | 535         |
| 30 DW             | 505         |
| 40 DW             | 450         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.