

TR 882

| | |
|---------------------------|--|
| TIRE SIZE | 400/60 - 15.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | PRESSE À PAILLE / MOISSONNEUSE / OUTILLAGE AGRICOLE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE / REMORQUE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 137 A8 |
| LI/SS FREE ROLLING | 149 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| CODE USA | 94029006 | RC (IN) | 102.6 |
| SW (IN) | 15.7 | RIM REC | AG 13.00 |
| OD (IN) | 34.4 | ECE | E11-106R-004334 |
| SLR (IN) | 14.9 | PR | 18 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 65 |
|-----------|-------|
| 5 FR | 10030 |
| 15 FR | 8530 |
| 20 FR | 8020 |
| 25 FR | 7160 |
| 5 DW | 7100 |
| 15 DW | 6030 |
| 20 DW | 5680 |
| 25 DW | 5070 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.