


# PL 801

<b>TIRE SIZE</b>	<b>7.00 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	RASTRILLO HILERADOR ROTATIVO / COSECHADORA / CARRETILLA ELEVADORA / COSECHADORA / MAQUINARIA AGRÍCOLA / CARRETILLA ELEVADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94007363	<b>RIM ALT</b>	5.50 BD; 5.5
<b>SW (IN)</b>	8.1	<b>PR</b>	14
<b>OD (IN)</b>	30.5		
<b>RIM REC</b>	6.0		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	145	150
<b>15 LOAD WHEEL</b>	6825	-
<b>15 STEER WHEEL</b>	5765	-
<b>5 OTHER VEHICLES</b>	5765	-
<b>15 OTHER VEHICLES</b>	4235	-
<b>STATIC SIDE LOADER</b>	-	9315

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.