

AS 504

TIRE SIZE	15.5/80 - 24
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	151 A8
LI/SS FREE ROLLING	163 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	384	RIM REC	W 12
OD (MM)	1262	RIM ALT	W 13; W 14 L
SLR (MM)	570	ECE	E4-106R-002265
RC (MM)	3875	PR	16

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
10 FR	6825
25 FR	5800
30 FR	5460
40 FR	4875
10 DW	4830
25 DW	4105
30 DW	3865
40 DW	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.