

EARTHMAX SR 423



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 423

EARTHMAX SR 423 is an All Steel radial tyre suitable for a variety of applications including quarry, haulage and logging operations. The non-directional tread pattern provides excellent traction and stability on any type of terrain. The tyre is ideal for handling heavy loads. The strong All Steel casing features excellent wear and resistance to snag and punctures. Its reinforced bead and the shoulder design contribute to an extended tyre life-cycle even under heavy-duty service conditions.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø20"	12.00 R 20	TT	-	18	154/150 J	8.50	9.00	0	302	1132			21,5	STD
Ø24"	325/95 R 24 (12.00 R 24)	TT	-	-	160/156 K	9.00	-	0	323	1243			21,5	STD
	12.00 R 24 (325/95 R 24)	TT	-	20	160/156 K	8.50	-	0	318	1243			21,5	STD
NEW	325/95 R 24 (12.00 R 24)	TL	-	-	167/164 F	9.00	-	0	323	1243			21,5	STD

STD: STANDARD

TECHNOLOGIES			PERFORMANCES		
					
					
K	167 kg				

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
325/95 R 24 (12.00 R 24)	TL	-	-	160/156 K	9.00	-	0	323	1243			21,5	STD
12.00 R 24 (325/95 R 24)	TL	-	20	160/156 K	8.50	-	0	318	1243			21,5	STD

STD: STANDARD



TECHNOLOGIES				PERFORMANCES		
						
K	167 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026