


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 7.00 - 12 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 88 A8 |
| LI/SS FREE ROLLING | 100 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94037308 | RC (IN) | 80.7 |
| SW (IN) | 7.4 | RIM REC | 4.5 |
| OD (IN) | 26.9 | ECE | E11-106R-003382 |
| SLR (IN) | 12.2 | PR | 8 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 48 |
|-----------|------|
| 5 FR | 2470 |
| 15 FR | 2090 |
| 20 FR | 1970 |
| 25 FR | 1760 |
| 5 DW | 1730 |
| 15 DW | 1470 |
| 20 DW | 1380 |
| 25 DW | 1230 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.