

# PL 801

<b>TIRE SIZE</b>	<b>18X7 - 8</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	РОТОРНЫЕ ГРАБЛИ / СЕНОВОРОШИЛКА / КОМБАЙН / ВИЛОЧНЫЙ ПОГРУЗЧИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ВИЛОЧНЫЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	173	<b>PR</b>	14
<b>OD (MM)</b>	470		
<b>RIM REC</b>	4.33 R		
<b>RIM ALT</b>	5.00 F		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>9.00</b>
<b>25 LOAD WHEEL</b>	1885
<b>25 STEER WHEEL</b>	1450
<b>10 OTHER VEHICLES</b>	1885
<b>25 OTHER VEHICLES</b>	1450
<b>STATIC SIDE LOADER</b>	2190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.