

FLOTATION 648

| | |
|---------------------------|---|
| TIRE SIZE | 385/65 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 148 A8/144 B |
| LI/SS FREE ROLLING | 160 A8/ 156 B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94006298 | RC (IN) | 127.3 |
| SW (IN) | 15.7 | RIM REC | AG 11.75 |
| OD (IN) | 42.1 | ECE | E4-106R-002263 |
| SLR (IN) | 18.7 | PR | 18 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 55 | 58 | 62 |
|--------------|-------|-------|-------|
| 5 FR | 12920 | 13320 | 13890 |
| 10 FR | 11630 | 11980 | 12500 |
| 20 FR | 10330 | 10660 | 11110 |
| 25 FR | 9230 | 9510 | 9920 |
| 30 FR | 8300 | 8560 | 8820 |
| 5 DW | 9040 | 9330 | 9720 |
| 10 DW | 8130 | 8390 | 8750 |
| 20 DW | 7230 | 7450 | 7780 |
| 25 DW | 6460 | 6660 | 6940 |
| 30 DW | 5810 | 6000 | 6170 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.