

EARTHMAX SR 30



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 30

EARTHMAX SR 30 (E-3/L-3) is an All Steel radial tyre which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	17.5 R 25	TL	E3/L3	**/*	167 B 176 A2	14.00/1.5	-	150	446	1347	606	4021	29	CR
	20.5 R 25	TL	L3	**	193 A2	17.00/2.0	17.00/1.7	0	529	1487	663	4439	32	CR
	26.5 R 25	TL	E3/L3	**/*	193 B 202 A2	22.00/3.0	-	230	689	1742	766	5200	38	CR
	26.5 R 25	TL	E3	**	193 B	22.00/3.0	-	230	689	1742	766	5200	38	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES		
					
E3/L3	B				
	216 kg				

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
15.5 R 25	TL	E3/L3	**/*	160 B 169 A2	12.00/1.3	-	130	397	1276	574	3809	27	CR
29.5 R 25	TL	L3	*	208 A2	25.00/3.5	-	0	765	1861	818	5555	42	CR
29.5 R 25	TL	E3/L3	**/*	200 B 208 A2	25.00/3.5	-	270	765	1861	818	5555	42	CR
23.5 R 25	TL	E3/L3	**/*	185 B 195 A2	19.50/2.5	-	200	612	1607	711	4797	34	CR
20.5 R 25	TL	E3/L3	**/*	177 B 186 A2	17.00/2.0	17.00/1.7	170	529	1487	663	4439	32	CR
26.5 R 25	TL	L3	*	202 A2	22.00/3.0	-	0	689	1742	766	5200	38	CR
29.5 R 25	TL	E3	**	200 B	25.00/3.5	-	270	765	1861	818	5555	42	CR
17.5 R 25	TL	L3	***	188 A2	14.00/1.5	-	0	446	1347	606	4021	29	CR
15.5 R 25	TL	L3	**	176 A2	12.00/1.3	-	-	397	1276	574	3809	27	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES			PERFORMANCES			
						
						

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
17.5 R 25	TL	L3	**	182 A2	14.00/1.5	-	-	446	1347	606	4021	29	CR
23.5 R 25	TL	L3	**	201 A2	19.50/2.5	-	-	612	1607	711	4797	34	CR
26.5 R 25	TL	L3	**	209 A2	22.00/3.0	-	-	689	1742	766	5200	38	CR
29.5 R 25	TL	L3	**	216 A2	25.00/3.5	-	-	765	1861	818	5555	42	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES			PERFORMANCES			
						
						
B	216 kg					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026